

3300X Legendary Reliability

Avoids Hand Contact With Push Paddle Taps

- Manual taps and lack of any PCB's or solenoids makes for easy maintenance
- Built on the same platform, and uses many of the same parts as the well known, ArcticChill88/98 and ArcticStar55
- The 3300X fits our overflow kit, our cowlings and mains drainage kit with or without pump



Push The Glass Or Cup
Against The Tap To
Dispense

Robust & Reliable
The Epitome
Of Perseverance

2468
YOU CAN COUNT ON US

3300X Legendary Reliability


Avoids Hand Contact With Push Paddle Taps

Accessories For The 3300X

Installation rail with filter. Includes compression fitting, 1-Micron green filter, water block, copper pressure reducing valve & non-return valve



Mains drainage - connect the drip tray to mains drainage. Can be supplied with a pump, to pump the water over 50m & a rise of 5m



Filter housing with carbon block candle & nanofilter



10 litre overflow system with alarm to signal when full. (Factory fitted)



Cowling to fix the cooler securely to the wall. (Supplied separately)



A pumped main drainage system pumps the waste water from the drip tray over a distance of 100m & a rise of 5m. (Factory installed)



3 Litre overflow kit connects the drip tray to a 3 litre alarmed overflow container. The container has a tap to empty without removing it



Description	Dimensions H x W x D mm	Weight
POU floor standing	1135 x 340 x 340	18
Bottled floor standing	1165 x 340 x 340	18
POU table top	460 x 340 x 340	15
Bottled table top	463 x 340 x 340	15

2468
YOU CAN COUNT ON US